
CIS/2 and IFC for Structural Steel




Robert Lipman
National Institute of Standards and Technology (NIST)
Computer Integrated Building Processes Group

cis2.nist.gov






What's the point of all this data exchange?





To avoid problems like this!







Information Representation for the Steel Supply Chain




What is CIS/2?

- CIMsteel Integration Standards
- Developed by Andrew Crowley and Alastair Watson at the Steel Construction Institute (UK)
- Adopted by the American Institute of Steel Construction (AISC) in 1998
- 15+ implementations import and/or export
- Implemented as file exchange, provides for DBMS
- Analysis, design, and detailed models
- Logical relationship between models
- Parts, assemblies, loads and reactions, materials, connections, drawing references, modification history, process information
- STEP is technical basis for CIS/2
- Schema described using Express language



Data Exchange Scenarios with the CIMsteel Integration Standards (CIS/2)





What's in a CIS/2 file (detailed model)

```
#43= LOCATED_PART(92,'92','brace',#42,#33,#20);
  #42= (COORD SYSTEM('', 'Part CS',$,3)
      COORD_SYSTEM_CARTESIAN_3D(#40)COORD_SYSTEM_CHILD(#18));
    #40= AXIS2_PLACEMENT_3D('Part axes', #34, #38, #36);
      #34= CARTESIAN POINT('Part origin',(0.,0.,0.));
      #38= DIRECTION('Part z-axis',(0.,0.,1.));
      #36= DIRECTION('Part x-axis',(1.,0.,0.));
    #18= COORD_SYSTEM_CARTESIAN_3D('','Assembly CS',$,3,#17);
      #17= AXIS2_PLACEMENT_3D('Assembly axes ',#11,#15,#13);
        #11= CARTESIAN_POINT('Assembly origin ',(720.,540.,120.));
        #15= DIRECTION('Assembly z-axis ',(-0.37139068,0.,0.92847669));
        #13= DIRECTION('Assembly x-axis ',(0.92847669,0.,0.37139068));
  #33= (PART(.UNDEFINED.,$)PART PRISMATIC()PART PRISMATIC SIMPLE(#21,#26,$,$)
      STRUCTURAL FRAME ITEM(92,'92','brace')STRUCTURAL FRAME PRODUCT($)
      STRUCTURAL FRAME PRODUCT WITH MATERIAL(#27,$,$));
    #21= SECTION PROFILE(1,'W14X158',$,$,5,.T.);
    #26= POSITIVE LENGTH MEASURE WITH UNIT
        (POSITIVE LENGTH MEASURE(258.48791), #3);
      #3= (CONTEXT DEPENDENT UNIT('INCH')LENGTH UNIT()NAMED UNIT(#1));
        #1= DIMENSIONAL EXPONENTS(1.,0.,0.,0.,0.,0.,0.);
    #27= MATERIAL(1, 'GRADE50',$);
  #20= LOCATED_ASSEMBLY(92,'92','brace',#18,$,#19,#10);
    #18= COORD SYSTEM CARTESIAN 3D('', 'Assembly Coordinate System', $, 3, #17);
      #17= AXIS2 PLACEMENT 3D('Assembly axes ', #11, #15, #13);
        #11= CARTESIAN POINT('Assembly origin ',(720.,540.,120.));
        #15= DIRECTION('Assembly z-axis ',(-0.37139068,0.,0.92847669));
        #13= DIRECTION('Assembly x-axis',(0.92847669,0.,0.37139068));
    #19= ASSEMBLY_MANUFACTURING(92,'92','brace',$,$,$,$,$,$);
    #10= STRUCTURE(1,'cis 2','Unknown');
```

Steel part defined by a cross section, length, and material





What's in a CIS/2 file (detailed model)

```
#43= LOCATED PART(92,'92','brace',#42,#33,#20);
  #42= (COORD SYSTEM('', 'Part CS',$,3)
      COORD_SYSTEM_CARTESIAN_3D(#40)COORD_SYSTEM_CHILD(#18));
    #40= AXIS2_PLACEMENT_3D('Part axes', #34, #38, #36);
                                                                              Locating the part in
      #34= CARTESIAN POINT('Part origin',(0.,0.,0.));
                                                                              an assembly
      #38= DIRECTION('Part z-axis',(0.,0.,1.));
      #36= DIRECTION('Part x-axis',(1.,0.,0.));
                                                                              Parts refer to
    #18= COORD_SYSTEM_CARTESIAN_3D('','Assembly CS',$,3,#17);
                                                                              assemblies
      #17= AXIS2_PLACEMENT_3D('Assembly axes ',#11,#15,#13);
        #11= CARTESIAN_POINT('Assembly origin ',(720.,540.,120.));
        #15= DIRECTION('Assembly z-axis ',(-0.37139068,0.,0.92847669));
        #13= DIRECTION('Assembly x-axis ',(0.92847669,0.,0.37139068));
  #33= (PART(.UNDEFINED.,$)PART PRISMATIC()PART PRISMATIC SIMPLE(#21,#26,$,$)
      STRUCTURAL FRAME ITEM(92,'92','brace')STRUCTURAL FRAME PRODUCT($)
      STRUCTURAL FRAME PRODUCT WITH MATERIAL(#27,$,$));
                                                                                   Steel part
                                                                                   defined by a
    #21= SECTION_PROFILE(1,'W14X158',$,$,5,.T.);
                                                                                   cross section,
    #26= POSITIVE LENGTH MEASURE WITH UNIT
                                                                                   length, and
        (POSITIVE LENGTH MEASURE(258.48791), #3);
      #3= (CONTEXT DEPENDENT UNIT('INCH')LENGTH UNIT()NAMED UNIT(#1));
                                                                                   material
        #1= DIMENSIONAL EXPONENTS(1.,0.,0.,0.,0.,0.,0.);
    #27= MATERIAL(1, 'GRADE50',$);
  #20= LOCATED_ASSEMBLY(92,'92','brace',#18,$,#19,#10);
    #18= COORD SYSTEM CARTESIAN 3D('', 'Assembly Coordinate System', $, 3, #17);
      #17= AXIS2 PLACEMENT 3D('Assembly axes ', #11, #15, #13);
        #11= CARTESIAN POINT('Assembly origin ',(720.,540.,120.));
        #15= DIRECTION('Assembly z-axis ',(-0.37139068,0.,0.92847669));
        #13= DIRECTION('Assembly x-axis ',(0.92847669,0.,0.37139068));
    #19= ASSEMBLY_MANUFACTURING(92,'92','brace',$,$,$,$,$,$);
    #10= STRUCTURE(1,'cis 2','Unknown');
```





What's in a CIS/2 file (detailed model)

```
#43= LOCATED PART(92,'92','brace',#42,#33,#20);
  #42= (COORD_SYSTEM('', 'Part CS',$,3)
      COORD_SYSTEM_CARTESIAN_3D(#40)COORD_SYSTEM_CHILD(#18));
    #40= AXIS2_PLACEMENT_3D('Part axes', #34, #38, #36);
      #34= CARTESIAN POINT('Part origin',(0.,0.,0.));
      #38= DIRECTION('Part z-axis',(0.,0.,1.));
      #36= DIRECTION('Part x-axis',(1.,0.,0.));
    #18= COORD_SYSTEM_CARTESIAN_3D('','Assembly CS',$,3,#17);
      #17= AXIS2_PLACEMENT_3D('Assembly axes ',#11,#15,#13);
        #11= CARTESIAN_POINT('Assembly origin ',(720.,540.,120.));
        #15= DIRECTION('Assembly z-axis ',(-0.37139068,0.,0.92847669));
        #13= DIRECTION('Assembly x-axis ',(0.92847669,0.,0.37139068));
  #33= (PART(.UNDEFINED.,$)PART PRISMATIC()PART PRISMATIC SIMPLE(#21,#26,$,$)
      STRUCTURAL FRAME ITEM(92,'92','brace')STRUCTURAL FRAME PRODUCT($)
      STRUCTURAL FRAME PRODUCT WITH MATERIAL(#27,$,$));
    #21= SECTION_PROFILE(1,'W14X158',$,$,5,.T.);
    #26= POSITIVE LENGTH MEASURE WITH UNIT
        (POSITIVE LENGTH MEASURE(258.48791), #3);
      #3= (CONTEXT DEPENDENT UNIT('INCH')LENGTH UNIT()NAMED UNIT(#1));
        #1= DIMENSIONAL EXPONENTS(1.,0.,0.,0.,0.,0.,0.);
    #27= MATERIAL(1, 'GRADE50',$);
  #20= LOCATED_ASSEMBLY(92,'92','brace',#18,$,#19,#10);
    #18= COORD SYSTEM CARTESIAN 3D('', 'Assembly Coordinate System', $, 3, #17);
      #17= AXIS2 PLACEMENT 3D('Assembly axes ', #11, #15, #13);
        #11= CARTESIAN POINT('Assembly origin ',(720.,540.,120.));
        #15= DIRECTION('Assembly z-axis ',(-0.37139068,0.,0.92847669));
        #13= DIRECTION('Assembly x-axis ',(0.92847669,0.,0.37139068));
    #19= ASSEMBLY_MANUFACTURING(92,'92','brace',$,$,$,$,$,$);
    #10= STRUCTURE(1,'cis 2','Unknown');
```

Locating the part in an assembly

Parts refer to assemblies

Steel part defined by a cross section, length, and material

Locating the assembly in an structure

Assemblies do not refer to parts





CIS/2 VRML Viewer

- Started development of the CIS/2 to VRML Translator 2000
- First presented at NASCC 2001
- Online web interface 2001
- Windows version 2003
- Software developers use it to verify their CIS/2 export
 - No need to exchange with other software
 - Resolve conflicts between software
 - Implement entities that are not imported by any software
- End users use it for design review, model sharing, electronic RFI, marketing, BOM, ...
- Tested with over 500 CIS/2 files
- Over 1000 downloads, 100s of upgrades from older versions
- Version 7.0 released November 2006
- Integration with 3D PDF, Google Earth, Google SketchUp




₽ CIS/	2 to VR	ML and IFC Trans	lator (6	.85)				DesignData3_ctv.wrl (model/vrml Object) - Mozilla Firefox
File Browsers Websites Help								
Status IFC Reports Detailed Other Colors Rendering VRML More VRML Debug								File Edit View Go Bookmarks Tools Help
✓ Ge Sch ○ 25 Sha ○ 1 ○ 2 ○ 3 Eler ○ 0 ○ 3	enerate an ema x3	2x 2x2-ST5 sentation rized Profiles (I, T, L, U, C, Profiles (ArbitraryClosed in Representation (B-rep) all esentation Column 1 - IfcBeam/C pElementProxy V Use	Z, Circle, Re istead of I, T, Il copes, see Column/Mem	ctangle L. U. C. Details ber (Centerl Z) some ed tab 2 - IfcN icable	w) Line) sor copes	ne copes	DesignData3_ctv.wrl (model/vr
Use Mapped Representation Use Ifc{Beam/Column/Member}Type More Options Detailed Model Assemblies: ○ IfcElementAssembly ○ IfcGroup ④ None Analysis Model: ☑ IfcStructuralAnalysisModel ☑ No Physical Model ☑ Analysis Map Design Model: ☑ Design Map Units: ④ Use Original ○ Convert to Millimeters ☑ Include Comments in IFC file ☐ IFC Viewer: Architectural Desktop 2006 ☑ Browse Done								Front Done
Translate Only Translate and Display Display Again List Options								Autodesk Architectural Desktop 2006 - [Drawing1.dwg] File Edit View Insert Format Window IFC-Utility Help □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
CIS/2 Summary Report - SDS/2 Training Seminar Model (JS) - Mozil								Aozil
le <u>E</u> dit <u>V</u> iew <u>G</u> o <u>B</u> ookmarks <u>T</u> ools <u>H</u> elp								
CIS/2 Summary Report - SDS/2 003-11-15 08:40:40-06:00								
art List	(Material List	t, <u>Assembly List,</u> <u>Bolt List</u>)						
Oty	/ Mark (Bold-main)	Size (Link to Material List)	Length (Ft-In)	Grade	Unit Wgt* (Lbs)	Total Wgt* (Lbs)	Function	
1 36	6 a1	L4x3-1/2x5/16	8 1/2	A36	5.4	195	Beam	(6) 13/16
2 6	6 a2	L3-1/2x3x5/16	0-10	A36	5.5	33	Beam	(6) 13/16
	6 a3	<u>L3-1/2x3x5/16</u>		A36	5.5	0.00	Beam	(6) 13/16
300	3 a4	<u>L3-1/2x3x5/16</u>		A36	7.2	22.22	Beam	(8) 13/16
222	3 a5	<u>L3-1/2x3x5/16</u>		A36	7.2	2 3000	Beam	(8) 13/16
6 24		L4x3-1/2x5/16	11 1/2	-	7.3		Beam	(8) 13/16
	5 a7	<u>L3-1/2x3x5/16</u>		A36	8.9		Beam	(10) 13/11
8 5	5 a8	<u>L3-1/2x3x5/16</u>	1-4	A36	8.9	44	Beam	(10) 13/11
y sta	art 4	<u>∌ </u>	🛭 🖟 CIS/2 t	o VRML	a	Auto	desk Archite	. S CIS/2 Summary B DesignData3_ctv LifanView I DesignData3_ctv

VRML model

IFC model







Denver Art Museum



Disney Concert Hall


VRML from CIS/2 files




















Soldier Field











What is IFC?

- Industry Foundation Classes (IFC) is the product data model developed by the IAI (International Alliance for Interoperability) to facilitate interoperability in the building industry
- Building information not geometry
- Extract information for design, analysis, facilities management, operation, quantity takeoff, energy simulation, code checking, cost estimating ...
- Well defined architecture and domain extension mechanism
- Current version IFC2x3
- IFC Certification
- Implementers Support Group (ISG), Modeling Support Group (MSG)





IFC Research

- Added CIS/2 to IFC translation 2005
- Identified deficiencies in IFC to handle structural steel, contributing to future versions of IFC
- Translator uses all IFC entities that can be used for structural steel (loads, reactions, bolts, welds, etc.)
- Provide IFC test cases for software developers of IFC importing applications
- End users moving CIS/2 models into IFC applications, for example RAM and SDS/2 to Revit and ArchiCAD to do coordination with concrete
- Contributing to future versions of the IFC schema
- Member of the IAI Structural Group, Implementers Support Group (ISG), Modeling Support Group (MSG)
- Developing Information Delivery Manual (IDM) for structural steel





What's in an IFC file

```
#147= IFCBEAM('OXNPpkfCnCVLy4HJ9X6tF_',#6005,'a2[1] L4x3-1/2x5/16','Located part',$,#119,#389,$);
  #6005= IFCOWNERHISTORY(#6003,#6004,$,.ADDED.,$,$,$,1109803792);
    #6003 = IFCPERSONANDORGANIZATION(#6001,#6002,$);
      #6001= IFCPERSON($,'Barry',$,$,$,$,$);
      #6002= IFCORGANIZATION($,'Design Data Corporation',$,$,$);
    #6004= IFCAPPLICATION(#6002, 'Unknown', 'SDS/2 Version 6.300 on NT', 'Unknown');
      #6002= IFCORGANIZATION($,'Design Data Corporation',$,$,$);
  #119= IFCLOCALPLACEMENT(#270,#241);
    #270= IFCLOCALPLACEMENT($,#239);
      #239= IFCAXIS2PLACEMENT3D(#164,#218,#217);
        #164= IFCCARTESIANPOINT((0.,0.,0.));
        #218= IFCDIRECTION((0.,0.,1.));
        #217= IFCDIRECTION((1.,0.,0.));
    #241= IFCAXIS2PLACEMENT3D(#170,#221,#220);
      #170= IFCCARTESIANPOINT((3048.,-3.30199987888336,-44.45));
      #221 = IFCDIRECTION((0.,-1.,0.));
      #220 = IFCDIRECTION((0.,0.,-1.));
  #389= IFCPRODUCTDEFINITIONSHAPE('a2[1]',$,(#390));
    #390= IFCSHAPEREPRESENTATION(#6011, 'Body', 'SweptSolid',(#391));
      #6011= IFCGEOMETRICREPRESENTATIONCONTEXT('Plan','Design',3,1.0E-5,#6040,$);
        #6040= IFCAXIS2PLACEMENT3D(#6041,#6042,#6043);
          #6041= IFCCARTESIANPOINT((0.,0.,0.));
          #6042= IFCDIRECTION((1.,0.,0.));
          #6043= IFCDIRECTION((0.,1.,0.));
      #391= IFCEXTRUDEDAREASOLID(#54,#6040,#6044,139.7);
        #54= IFCLSHAPEPROFILEDEF(.AREA.,'L4X3-1/2X5/16',#304,101.6,88.9,7.9,11.1,$,$,44.45,50.8);
          #304= IFCAXIS2PLACEMENT2D(#303,#6052);
            #303= IFCCARTESIANPOINT((-44.45,50.8));
            #6052= IFCDIRECTION((1.,0.));
        #6040= IFCAXIS2PLACEMENT3D(#6041,#6042,#6043);
          #6041= IFCCARTESIANPOINT((0.,0.,0.));
          #6042= IFCDIRECTION((1.,0.,0.));
          #6043= IFCDIRECTION((0.,1.,0.));
        #6044= IFCDIRECTION((0.,0.,1.));
```

Steel part is a beam (or column, member)

Locating the part in an assembly and assembly in the structure


Other entities group parts in an assembly

Geometry of steel part defined by a cross section and length (or boundary representation)


Other entities associate materials













- < analysis model
- < assemblies
- < bolts






NIST Large Fire Research Facility Emissions Control System (ECS)

- •Fire tests in building (right)
- •Steel structure carries ducts to ECS (left)
- •Steel detailed in SDS/2 and exported to CIS/2







VRML from CIS/2 translator (multicolored) Building, ductwork, ECS generated by hand


















IFC file import







NIST_ctv31m_2x3.dgn (3D - V8 DGN) - Bentley Structural V8 XM Edition








IFC file import











Coordination of steel (from CIS/2) and concrete in Revit








Coordination of steel (from CIS/2) and concrete in Revit







Coordination of steel (from CIS/2) and concrete in Revit








IFC Issues for Structural Steel


- In the previous slides, the same IFC file could not be imported into the IFC applications because of sometimes incomplete implementation of parametric profiles, one size (file) does not fit all
- Parametric profiles are essential for structural steel
- Information relevant to structural steel is lost, misplaced, or ignored when imported (piecemark, section designator, cardinal point), need agreement where that information will go
- Some things not handled well or at all or not imported: parametric profiles, bolts, welds, holes, some loads, mirrored sections, double angles, cutouts, item properties
- CIS/2 has strong notion of an assembly (main beam/column + clip angles, gusset plates)
- Explicit geometry (IFC) vs. implicit geometry (CIS/2)
- Roundtripping issues, input as parametric profile, export as B-rep, adding extra coordinate transforms
- Vendor specific property sets







- Next version trees became chairs
- Next version nothing displayed
- Should be corrugated decking






Technology Administration, U.S. Department of Commerce



Corrugated decking is correct







For more information:

cis2.nist.gov

